

ACT-26



Automatic Cut & Transfer - Coiling & Spooling

Equipment Benefits:

- Automatic Cut & Transfer
- Precision Military Winding
- Improved Production 1000 FPM
- Automatic Stretch Wrap
- Best Tension Control
- Lowest Maintenance
- No Belts, Gears or Pulleys
- Quiet, Fast, Smooth



Model ACT-26




The ACT System Offers:

- Higher standard speeds reaching 1000 fpm.
- Best available package quality with servo driven indexing turret and material guide arm.
- Superior safety with a standard “S” guard isolating the operator from the “run” side and optional full guarding with failsafe interlocks.
- Precise speed and tension controls with use of dancer loop.
- Highly flexible and reliable application specific customization, operating on and offline wire and cable, medical tubing and plastic profile on applications.
- Innovative Flexible Material Spooling & Coiling Solutions
- Traversing Stretch Wrap Cartridge up to 21” Wide
- Articulate Guide Servo Axis
- Replaceable Entrance Product Guides

Available Options:



AUTOMATIC COILING HEADS



AUTOMATIC BANDING AND EJECTION



AUTOMATIC STRETCH WRAP

REELPOWER
INDUSTRIAL

5101 S. Council Road, Suite 100 • Okla. City, OK. 73179


405.672.0000 • 405.672.7200 Fax

www.reelpowerind.com

ACT-26




Automatic Cut & Transfer - Coiling & Spooling



INTEGRATED GRIPPER CUTTER

Innovative Flexible Material Spooling & Coiling Solutions



TRAVERSING STRETCH WRAP CARTRIDGE UP TO 21" WIDE.



ARTICULATE GUIDE SERVO AXIS



REPLACEABLE ENTRANCE PRODUCT GUIDES



MODEL / DIMENSIONS	ACT-16	ACT-26	ACT-36
MAX DIAMETER INCH (MM)	16 in (407 mm)	26 in (660 mm)	36 in (914 mm)
MAX WIDTH INCH (MM)	12 in (305 mm)	16 in (406 mm)	24 in (610 mm)
MAX HEIGHT LBS (KG)	50 lbs (23 kg)	150 lbs (68 kg)	400 lbs (181 kg)
A	65 in (1651 mm)	85 in (2159 mm)	118 in (2997 mm)
B	60 in (1524 mm)	67 in (1702 mm)	47 in (1880 mm)
C	64 in (1626 mm)	89 in (2260 mm)	106 in (2692 mm)