

# ACT-36

## *Automatic Cut & Transfer - Coiling & Spooling*

### **Equipment Benefits:**

- Automatic Cut & Transfer
- Precision Military Winding
- Improved Production 1000 FPM
- Automatic Stretch Wrap
- Best Tension Control
- Lowest Maintenance
- No Belts, Gears or Pulleys
- Quiet, Fast, Smooth



### **Model ACT-36**



### **The ACT System Offers:**

- Higher standard speeds reaching 1000 fpm.
- Best available package quality with servo driven indexing turret and material guide arm.
- Superior safety with a standard “S” guard isolating the operator from the “run” side and optional full guarding with failsafe interlocks.
- Precise speed and tension controls with use of dancer loop.
- Highly flexible and reliable application specific customization, operating on and offline wire and cable, medical tubing and plastic profile on applications.
- Innovative Flexible Material Spooling & Coiling Solutions
- Traversing Stretch Wrap Cartridge up to 21” Wide
- Articulate Guide Servo Axis
- Replaceable Entrance Product Guides

### **Available Options:**



**AUTOMATIC COILING HEADS**



**AUTOMATIC BANDING AND  
EJECTION**



**AUTOMATIC STRETCH WRAP**

**REELPOWER**  
INDUSTRIAL


5101 S. Council Road, Suite 100 • Okla. City, OK. 73179

405.672.0000 • 405.672.7200 Fax

[www.reelpowerind.com](http://www.reelpowerind.com)

# ACT-36

## Automatic Cut & Transfer - Coiling & Spooling



**INTEGRATED GRIPPER  
CUTTER**

### Innovative Flexible Material Spooling & Coiling Solutions



**TRAVERSING STRETCH WRAP  
CARTRIDGE UP TO 21" WIDE.**



**ARTICULATE GUIDE  
SERVO AXIS**



**REPLACEABLE ENTRANCE  
PRODUCT GUIDES**

#### Additional Features Provided:

- Cutter and heavy-duty grippers
- Recipe Management - Programmable recipe management Ethernet or local flash drive. This allows customer to store product info to easily change programming for a number of products automatically.
- Pneumatic actuated release for material clamping device.
- CRS Tubing Guide Arms -
- Allen-Bradley Controls Package - Controls and Servos
- Machine guarding
- Left to Right Configuration

MODEL / DIMENSIONS	ACT-16	ACT-26	ACT-36
MAX DIAMETER INCH (MM)	16 in (407 mm)	26 in (660 mm)	36 in (914 mm)
MAX WIDTH INCH (MM)	12 in (305 mm)	16 in (406 mm)	24 in (610 mm)
MAX HEIGHT LBS (KG)	50 lbs (23 kg)	150 lbs (68 kg)	400 lbs (181 kg)
A	65 in (1651 mm)	85 in (2159 mm)	118 in (2997 mm)
B	60 in (1524 mm)	67 in (1702 mm)	47 in (1880 mm)
C	64 in (1626 mm)	89 in (2260 mm)	106 in (2692 mm)