

ACT-36



Automatic Cut & Transfer - Coiling & Spooling

Equipment Benefits:

- Automatic Cut & Transfer
- Precision Military Winding
- Improved Production 1000 FPM
- Automatic Stretch Wrap
- Best Tension Control
- Lowest Maintenance
- No Belts, Gears or Pulleys
- Quiet, Fast, Smooth



Model ACT-36



The ACT System Offers:

- Higher standard speeds reaching 1000 fpm.
- Best available package quality with servo driven indexing turret and material guide arm.
- Superior safety with a standard “S” guard isolating the operator from the “run” side and optional full guarding with failsafe interlocks.
- Precise speed and tension controls with use of dancer loop.
- Highly flexible and reliable application specific customization, operating on and offline wire and cable, medical tubing and plastic profile on applications.
- Innovative Flexible Material Spooling & Coiling Solutions
- Traversing Stretch Wrap Cartridge up to 21” Wide
- Articulate Guide Servo Axis
- Replaceable Entrance Product Guides

Available Options:



AUTOMATIC COILING HEADS



AUTOMATIC BANDING AND EJECTION




AUTOMATIC STRETCH WRAP

ACT-36



Automatic Cut & Transfer - Coiling & Spooling



INTEGRATED GRIPPER CUTTER

Innovative Flexible Material Spooling & Coiling Solutions



TRAVERSING STRETCH WRAP CARTRIDGE UP TO 21" WIDE.



ARTICULATE GUIDE SERVO AXIS



REPLACEABLE ENTRANCE PRODUCT GUIDES

Additional Features Provided:

- Cutter and heavy-duty grippers
- Recipe Management - Programmable recipe management Ethernet or local flash drive. This allows customer to store product info to easily change programming for a number of products automatically.
- Pneumatic actuated release for material clamping device.
- CRS Tubing Guide Arms -
- Allen-Bradley Controls Package - Controls and Servos
- Machine guarding
- Left to Right Configuration

MODEL / DIMENSIONS	ACT-16	ACT-26	ACT-36
MAX DIAMETER INCH (MM)	16 in (407 mm)	26 in (660 mm)	36 in (914 mm)
MAX WIDTH INCH (MM)	12 in (305 mm)	16 in (406 mm)	24 in (610 mm)
MAX HEIGHT LBS (KG)	50 lbs (23 kg)	150 lbs (68 kg)	400 lbs (181 kg)
A	65 in (1651 mm)	85 in (2159 mm)	118 in (2997 mm)
B	60 in (1524 mm)	67 in (1702 mm)	47 in (1880 mm)
C	64 in (1626 mm)	89 in (2260 mm)	106 in (2692 mm)