

GANTRY TAKE-UPS & PAYOFFS

GTU Series 2.5 to 15 Ton



UNIT FEATURES:

- Integrated safety features
 - o Safety Scanners
 - o Integrated Guarding
 - o Camera
 - o Integrated Safety Lock-Out system
- Smart-phone compatibility
- Integrated Maintenance Ports
- Networkable

ZERO MATERIAL FLEETING ANGLE

- Superior level-wind capabilities
- Tandem operation allows for continuous line operation and offers faster and more convenient loading
- Minimized line lengths even with large, non-flexible material
- Processes round, flat and rectangular products

SUPERIOR CONTROLS

- Standard controls fit all applications of dancer, speed, or torque controls with selectable diameter and line speed compensation.
- Color touchscreen on take-up and payoff allows complete operator control and maintenance access
- Independent load control stations for convenient load access

TELESCOPING FRAME CONFORMS TO THE ACTUAL REEL SIZE

- Offers true roll thru capabilities
- Increased productivity
- Improved bolt-on arbor cone design

OPTIONAL

- Rim Driven Systems
- Overhead beam design
- Auto reel loading
- Zero fleeting angle payoffs
- Integrated Optical Scanner

Standard Models and Specifications

MODEL	Flange Diameter MIN / MAX in(mm)	Outside Width MIN / MAX in(mm)	Weight Capacity T/lbs
GTU/GPO-5	28 (711) / 72 (1,829)	24 (610) / 48 (1,219)	2.5 / 5,000
GTU/GPO-10	30 (762) / 96 (2,438)	30 (762) / 54 (1,372)	5 / 10,000
GTU/GPO-15	36 (915) / 96 (2,438)	36 (915) / 67 (1,702)	7.5 / 15,000
GTU/GPO-20	36 (915) / 96 (2,438)	36 (915) / 67 (1,702)	10 / 20,000
GTU/GPO-30	36 (915) / 96 (2,438)	36 (915) / 67 (1,702)	15 / 30,000

REELPOWER
WIRE & CABLE

5101 S. Council Road, Suite 100 • Okla. City, OK. 73179
405.672.0000 • 405.672.7200 Fax

www.reelpowerwc.com