# **HJP SERIES PAY-OUTS**

### Mobile Pay-Out Machinery

Recommended for use with paying out material from supply reels. The HJP can improve the efficiency of your reel and cable handling operation. By utilizing a hydraulic jack (standard) or ElectroLift, reels can be raised and lowered with ease, using minimal manpower.



Model HJ5P shown above with a 10" mechanical tension brake



5101 S. Council Road, Suite 100 • Okla. City, OK. 73179 405.672.0000 • 405.672.7200 Fax www.reelpowerind.com

## **HJP SERIES PAY-OUTS**


## Mobile Pay-Out Machinery

#### **Optional Benefits**

- Powered Pay-out Feature
- Bolt-on Auxiliary Fork Tips
- Mechanical Disc Tension Brake
- Electromagnetic Tension Brake
- ElectroLift (Electric/Hydraulic Reel Lifting)
- •Special Shaft Bushings
- Measuring Meter
- Manual Shaftless Feature



10" Mechanical Brake



Front mounted load controls



120 Volt Panel Box



5101 S. Council Road, Suite 100 • Okla. City, OK. 73179 405.672.0000 • 405.672.7200 Fax www.reelpowerind.com

### Standard Reel Capacities:

HJP	20"	to	48"	dia.,	36"	wide	Х	2,500	lbs.

- **HJ3P** 20" to 54" dia., 38" wide X 3,000 lbs.
- **HJ4P** 30" to 60" dia., 38" wide X 4,000 lbs.
- **HJ5P** 38" to 72" dia., 48" wide X 5,000 lbs.
- HJ8P38" to 84" dia., 60" wide X 8,000 lbs.\*HJ10P40" to 96" dia., 60" wide X 10,000 lbs.\*

\*Units not equipped with ElectroLift include a manual hydraulic lift jack

HJP15	36" to 108" dia., 72" wide X 15,000 lbs.					
HJP20	66" to 120" dia., 72" wide X 20,000 lbs.					
HJ15 & HJ20 include ElectroLift as standard equipment.						